

LESCO®

GREEN TURF PAINT

Restores a Natural Green Color
to Dormant or Discolored Turf

- Adds look of health and beauty to warm and cool season turfgrasses.
- Will not wash off or wear off turf.
- Fall application on dormant turf lasts through winter
- Recommended for use on athletic fields, golf course greens, tees and fairways, commercial and residential lawns.
- Easy spray application through any type of conventional sprayer.
- In-season application for discolored or stressed grass.
- Non-phytotoxic – will not harm grass plants.

#008423

Net Content: 2.5 gallons (9.46 Liters)



7

TM

LESCO, Inc. • 1385 East 36th Street • Cleveland, OH 44114-4114

2LBL000299 rev. 06/10

DESCRIPTION

LESCO Green is a permanent green pigment which will not injure turfgrass. It can be applied at any time during the year to beautify discolored turf. Grass can instantly become green when it is dormant, LESCO Green provides a natural green and healthy appearance to even the brownest grasses. It can also be added to golf course sand to create a green divot mix for top dressing.

DIRECTIONS FOR USE

SHAKE WELL BEFORE USE. Before applying LESCO Green, mow turfgrass area to desired height. One gallon of LESCO Green will cover 5,000 to 12,000 sq. ft. depending on type of spray equipment, condition and species of grass, mowing height, and desired color. Shorter mowing height and finer spray droplets will require the least volume of spray necessary for complete coverage.

For fall or winter application on dormant turf, dilute 1 gallon of LESCO Green with 10 to 20 gallons of water (6-12 oz./gal. of spray). This equals approximately 10 oz. LESCO Green per 1,000 sq. ft. Flat fan or cone nozzles producing fine droplet sizes will result in best turf canopy coverage. Two perpendicular applications are recommended to produce best color results.

For summer applications on discolored turf, dilute 1 gallon of LESCO Green with 15 to 25 gallons of water (5-8 oz./gal. of spray). This equals approximately 8 oz. LESCO Green per 1,000 sq. ft. Two perpendicular applications are recommended to produce best color results.

Do not apply LESCO Green when wind conditions favor drift. This is a permanent pigment and will adhere to any dry surface. Use only Teflon seals in centrifugal pumps to prevent leaks that may occur with ceramic seals. This type of flowable colorant may wear pump seals.

To color divot mix, spray LESCO Green onto sand as it is being mixed in a small cement-type mixer, wheel barrow, etc. Mix 6 oz. of LESCO Green with 100 lb. of sand to obtain a green colored divot mix.

STORAGE AND DISPOSAL

Keep from freezing. Do not re-use empty container. Safety goggles are recommended when handling the concentrate. If product is spilled, contain and absorb with inert material. Dispose of in accordance with local, state, and federal regulations.

KEEP OUT OF REACH OF CHILDREN CAUTION

Do not take internally. In case of eye contact, flush with large amounts of water and consult a physician. In case of ingestion, dilute with water or milk and consult a physician.

CONDITION OF SALE AND LIMITATION OF WARRANTY AND LIABILITY

NOTICE: Read the entire Directions for Use and Conditions of Sale and Limitation of Warranty and Liability before buying or using this product. If the terms are not acceptable, return the product at once, unopened, and the purchase price will be refunded.

The Directions for Use of this product must be followed carefully and completely. It is impossible to eliminate all risks inherently associated with the use of this product. Buyer and/or User assume all risks of ineffectiveness or other unintended consequences or damages that may result from conditions outside or beyond the control of LESCO, Inc. including but not limited to such factors as manner of use or application, weather or weather conditions outside the range considered normal at the application site or for the time period in which the product is applied, the presence of other materials, incompatible products, or other influencing factors which are beyond the control of LESCO, Inc.. All such risks shall be assumed by Buyer and/or User, and Buyer and/or User agrees to hold LESCO, Inc. harmless for any claims relating to such factors.

LESCO, Inc. warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated in the Directions for Use, subject to the inherent risks referred to above, when used in accordance with the Directions for Use under normal use conditions. This warranty does not extend to the use of this product contrary to label instructions, or under abnormal conditions or under conditions not reasonably foreseeable to or beyond the control of LESCO, Inc. and Buyer and/or User assume the risk of any such use.

LESCO, INC. MAKES NO WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE NOR ANY OTHER EXPRESS OR IMPLIED WARRANTY EXCEPT AS STATED ABOVE.

THE EXCLUSIVE REMEDY OF THE BUYER AND/OR USER AND THE EXCLUSIVE LIABILITY OF LESCO, INC. FOR ANY AND ALL CLAIMS, LOSSES, INJURIES OR DAMAGES (INCLUDING CLAIMS BASED ON BREACH OF WARRANTY, CONTRACT, NEGLIGENCE, TORT, STRICT LIABILITY OR OTHERWISE) RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, SHALL BE THE RETURN OF THE PURCHASE PRICE OF THE PRODUCT OR, AT THE ELECTION OF LESCO, INC. REPLACEMENT OF THE PRODUCT, OR IF NOT ACQUIRED BY PURCHASE, REPLACEMENT OF SUCH QUANTITY. IN NO EVENT SHALL LESCO, Inc., BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES.

LESCO, Inc. offers this product, and Buyer and/or User accepts it, subject to the foregoing Conditions of Sale and Limitation of Warranty and Liability, which may not be modified except by written agreement signed by a duly authorized representative of LESCO, Inc.

© Copyright 2001 LESCO, and the Sweeping Design are trademarks of
LESCO Technologies, LLC.

2LBL000947 Rev. 6/10